



Technical Data Sheet: CR94018

Product manual **CR94018** is a silica matting agent. It has the characteristics of high matting efficiency, good transparency, easy to add and disperse. It is especially suitable for wood furniture, decoration paint system, printing ink and industrial paint, plastic film coating, coil coating for matting.

Product features

- High matting efficiency
- Good transparency
- Easy to add and disperse

Recommended use

- Wooden furniture
- Paint coating system for decoration
- Print ink and industrial paint, plastic film coating, coil coating for dullness

Specifications	Appearance(By vision)	White powder	PH (5% suspension)	6.0-7.0
	Mean particle size (laser um)	5.0-5.5	Whiteness	93
	Dry loss on weight (105℃,%)	5.5	Porosity (ml/g)	1.8-2.0
	Loss on ignition (1000℃,%)	5.0	Silica content (%)	99.0
	DBP oil absorption value	240-300	Surface preparation	-
	(g/100g)			

Packing The net content of kraft paper composite bag is 10KG.

Storage conditions Please keep cool or dry place, and avoid sun and heat;
Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.

Use matters

It is recommended that customers take necessary protective measures during loading, unloading, use and transportation to avoid dust flying.

It is recommended that the stacking height should not exceed 10 layers and the dispersion time should be appropriately extended due to compression affecting product dispersion.

It is recommended that the product should be unpacked and used immediately to avoid the use effect affected by moisture.